

Control4® T3 Series Tabletop Touch Screens



Control4 T3 Series Tabletop Touch Screens (C4-TT7-1-BL, C4-TT7-1-WH, C4-TT7-1-RD, C4-TT10-BL, C4-TT10-WH)

The Control4® T3 Series Tabletop Touch Screen delivers always-on, dedicated, and mobile control over all the technology in your home or business. Featuring a gorgeous new tablet design and stunning high-resolution graphics, this portable screen looks beautiful whether on a kitchen countertop or in the theater on your lap. This model includes HD video intercom and crystal-clear audio intercom for convenient communications from room to room or with visitors at the door.

- Available in 7" and 10" models, the T3 Series Portable Touch Screen provides dedicated, elegant, and mobile control of your home.
- HD camera, combined with speakers and microphone, provides the best video intercom experience yet.
- Crisp picture with two and a half times the resolution of previous models.
- Extremely fast and responsive—up to 16 times faster than our previous Touch Screens.
- Easily configured as a true portable or as a tethered tabletop for flexible installation.
- Wired and wireless connections through Wireless-N and 10/100 Ethernet.
- Flexible power options with AC power supply adapter, Power over Ethernet (PoE), or internal battery.
- Video intercom integration with the following Door Stations and Touch Screens: Door Station (C4-DSC-EN) and DS2 Door Station (C4-DS2), T3 Series In-Wall Touch Screens (C4-WALL7, C4-WALL10), and legacy Touch Screens (C4-TW7CO, C4-TSMC7).
- Audio intercom integration with the legacy Door Station (C4-DSC-EN) and DS2 Door Station (C4-DS2), and the following Touch Screens: T3 Series In-Wall Touch Screens (C4-WALL7, C4-WALL10) and legacy Touch Screens (C4-TW7CO, C4-TSMC7, C4-TSWMC5, C4-TSWMC7).
- Available in gloss white, black, and red (7" model only).

Control4® Tabletop Touch Screens

Model numbers	C4-TT7-1-BL, C4-TT7-1-WH, C4-TT7-1-RD, C4-TT10-BL, C4-TT10-WH
Features	
Screen	Resolution: 1280 × 800 Capacitive touch Camera: 720p
Network	Ethernet or WiFi (802.11 g/n [2.4 GHz]) Notes: (1) 802.11b is not supported for Video Intercom. (2) Wireless-N is recommended for Video Intercom. The more devices that Video Intercom is broadcast to, the more response time and images are degraded.
Battery	7": 3,100 mAh Li-ion 10": 7,000 mAh Li-ion
Power supply	PoE (IEEE802.3af) 100VAC ~ 240VAC, 50-60 Hz International power supply adapters included
Charging station connections	<ul style="list-style-type: none"> • Ethernet • PoE • DC power
Mounting	Tabletop or portable
Environmental	
Operating temperature	32 - 104°F (0° - 40°C)
Storage temperature	32 - 104°F (0° - 40°C)
Dimensions (W × H × D)	7" Touch Screen: 7.0 × 5.1 × 0.75" (178 × 130 × 19 mm); 10" Touch Screen: 9.65 × 6.77 × 0.91" (245 × 172 × 23 mm) 7" charging station: 4.17 × 3.11 × 2.21" (106 × 79 × 56 mm); 10" charging station: 4.53 × 4.02 × 2.60" (115 × 102 × 66 mm)
Weight	7" Touch Screen: 0.7 lbs. (0.32 kg); 10" Touch Screen: 1.35 lbs. (0.60 kg) 7" charging station: 0.8 lbs (0.36 kg); 10" charging station: 1.05 lbs. (0.46 kg)

Planning the installation

- Make sure the charging station can be located near a power outlet and a strong WiFi signal.
- For the most reliable connection, we recommend running Ethernet to the charging station.
- Make sure the touch screen's WiFi or Ethernet connection is on the same network as your controller and that the signal is strong.
- Communication agent is required for intercom use.
- Charge the touch screen for at least six hours before use.

For more product information

Visit ctrl4.co/t3series

